

Servo amplifier

mcDSA-B65

Article number: 1504907



Picture similar

Technical data

Power	
Electronic supply voltage Ue	9..30 V
Electronic current consumption @ Ue=24V	typ. 30 mA
Power supply voltage Up	9..60 V
Max. output current	15 A
Continuous output current	5 A
Output voltage	100% Up
PWM frequency	25 kHz
Min. load inductance	200 uH
Mechanical	
Size LxWxH	74 x 45.5 x 14 mm
Weight	30 g
Environment	
Protection class	IP20
Operating temperature	0..70 °C
Rel. humidity (non-condensing)	5..85 %
Hall sensors	
Signals	H1,H2,H3
Max. frequency (per channel)	10 kHz
Input voltage	5 V
Signal type	open collector, single ended
Digital inputs	
Number	3 (Din0..2)
Low voltage	-10..5 V
High voltage	6..30 V
Notice	Din2 parallel with Dout0
Digital outputs	
Number	1 (Dout0)
Continuous output current	1.5 A
Load	resistive, induktive
Output voltage	Electronic supply voltage Ue
Signal type	positive switching
Notice	Dout0 parallel with Din2
Analog inputs	

* default value

Additional technical data are available in mcManual.

Number	1 (Ain0)
Signal type	+/- 10 V, 12 Bit, single ended
CAN bus	
Protocol	DS301
Max. baudrate	1 Mbit/s
CAN specification	2.0B
Galvanically isolated	no

Scheme



Terminal assignment

X1	Hall, I/O's and CAN	
1	GND	Ground for 5V auxiliary voltage (hall)
2	+U5V	5V auxiliary voltage (hall)
3	res.	Reserved
4	res.	Reserved
5	H3	Hall sensor 3
6	H2	Hall sensor 2
7	H1	Hall sensor 1
8	CAN Lo	CAN Low
9	CAN Hi	CAN High
10	Din2/Dout0	Digital input 2 / Digital output 0
11	Din1	Digital input 1
12	Din0	Digital input 0
13	Ain0	Analog input 0
14	GND	Ground for electronic supply voltage
15	+Ue	Electronic supply voltage
X2	Motor	
1	+Up	Power supply voltage
2	GND	Ground for power supply voltage
3	Ma	Motor phase A
4	Mb	Motor phase B
5	Mc	Motor phase C