



减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512
额定承载扭矩 (Rated load torque)	Nm	260	230	120
最大加速力矩 (Max. acceleration torque)	Nm	468	414	216
急停扭矩 (Emergency stop torque)	Nm	780	690	360

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机技术参数				精密行星减速机	
容许最大径向载荷 (Max. radial load)	1850N	空载力矩20°C (No-load torque)	$\leq 0.36$ Nm	Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	2800N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15°C~+90°C		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000$ h	PL120L3-i-P2-S2	
噪音 (Noise)	$\leq 63$ db	防护等级 (Protection grade)	IP54	22-58-110-145-M8	
回程间隙 (Backlash)	14arcmin	PL系列	Tel/电话: 0533-6288333 6288444	A. PL. 120.	
		P2 L3	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		