



精密行星减速机技术参数				未注线性尺寸极限偏差 Unmarked tolerance	
减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	0.5-3 ± 0.2
额定承载扭矩 (Rated load torque)	Nm	45	41	18	3-6 ± 0.3
最大加速力矩 (Max. acceleration torque)	Nm	81	73.8	32.4	6-30 ± 0.5
急停扭矩 (Emergency stop torque)	Nm	135	123	54	30-120 ± 0.8
					120-400 ± 1.2
					400-1000 ± 2
精密行星减速机技术参数				精密行星减速机	
容许最大径向载荷 (Max. radial load)	480N	空载力矩20°C (No-load torque)	≤ 0.1 Nm		
容许最大轴向载荷 (Max. axial load)	600N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	$-15^{\circ}\text{C} \sim +90^{\circ}\text{C}$		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥ 20000 h		
噪音 (Noise)	≤ 60 db	防护等级 (Protection grade)	IP54		
回程间隙 (Backlash)	14arcmin		PL系列		
			P2 L3		
			A. PL. 060.		



PL.060L3-i-P2-S2
14-30-50-70-M5

A. PL. 060.